



Concentric & Eccentric Reducers
STANDARD WEIGHT
 Inches / Pounds



Concentric



Eccentric

Nominal Pipe Size	Length (H)	Approximate Weight (in Pounds)
3/4 x 1/2	1	.21
1 x 1/2	2	.36
1 x 3/4	2	.36
1 1/4 x 1/2	2	.42
1 1/4 x 3/4	2	.42
1 1/4 x 1	2	.48
1 1/2 x 1/2	2.5	.56
1 1/2 x 3/4	2.5	.56
1 1/2 x 1	2.5	.57
1 1/2 x 1 1/4	2.5	.65
2 x 3/4	3	.74
2 x 1	3	.81
2 x 1 1/4	3	.88
2 x 1 1/2	3	.94
2 1/2 x 1	3.5	1.3
2 1/2 x 1 1/4	3.5	1.4
2 1/2 x 1 1/2	3.5	1.5
2 1/2 x 2	3.5	1.6
3 x 1	3.5	1.7
3 x 1 1/4	3.5	1.8
3 x 1 1/2	3.5	1.9
3 x 2	3.5	2.0
3 x 2 1/2	3.5	2.2
3 1/2 x 1 1/4	4	2.5
3 1/2 x 1 1/2	4	2.6
3 1/2 x 2	4	2.6
3 1/2 x 2 1/2	4	2.7
3 1/2 x 3	4	2.8

Concentric & Eccentric Reducers – Standard Weight *(Continued)*

Nominal Pipe Size	Length (H)	Approximate Weight (in Pounds)
4 X 1	4	2.8
4 X 1 ¼	4	3
4 x 1 ½	4	3
4 x 2	4	3.1
4 x 2 ½	4	3.2
4 x 3	4	3.3
4 x 3 ½	4	3.5
5 X 2	5	4.7
5 X 2 ½	5	4.8
5 X 3	5	5.1
5 X 3 ½	5	5.3
5 X 4	5	5.5
6 X 2	5.5	6.5
6 X 2 ½	5.5	6.6
6 X 3	5.5	6.9
6 X 3 ½	5.5	7.1
6 X 4	5.5	7.4
6 X 5	5.5	7.6
8 X 3	6	9.8
8 X 3 ½	6	10.6
8 X 4	6	10.8
8 X 5	6	11.5
8 X 6	6	12.3
10 X 4	7	18.4
10 X 5	7	19.5
10 X 6	7	20.7
10 X 8	7	22.1
12 X 4	8	26.2
12 X 5	8	27.8
12 X 6	8	29.5
12 X 8	8	30.5
12 X 10	8	32.4
14 X 6	13	59.2
14 X 8	13	60.0
14 X 10	13	61.4
14 X 12	13	63.1

Concentric & Eccentric Reducers – Standard Weight *(Continued)*

Nominal Pipe Size	Length (H)	Approximate Weight (in Pounds)
16 X 6	14	67.4
16 X 8	14	69.4
16 X 10	14	71.1
16 X 12	14	72.7
16 X 14	14	75.4
18 X 10	15	83.7
18 X 12	15	84.8
18 X 14	15	86.0
18 X 16	15	87.3
20 X 10	20	117
20 X 12	20	118
20 X 14	20	119
20 X 16	20	121
20 X 18	20	123
24 X 10	20	141
24 X 12	20	144
24 X 14	20	147
24 X 16	20	150
24 X 18	20	153
24 X 20	20	156
30 X 18	24	315
30 X 20	24	315
30 X 24	24	315
36 X 20	24	379
36 X 24	24	379
36 X 30	24	379
42 X 24	24	443
42 X 30	24	443
42 X 36	24	443
48 X 30	28	525
48 X 36	28	525
48 X 42	28	525

** Dimensions conform to ASME B16.9 & material conforms to ASTM SA-234 Grade B.*